



"BS" BACKSET	"SL" SHOOT LENGTH	"FB" FACEBAR WIDTH	"L" LENGTH		"OL" OVERALL LENGTH		PART NUMBER	SHOOT TIP EXTENSION	
			MIN	MAX	MIN	MAX			
35mm (1.378")	20mm (.787")	16mm (.630")	59.762	73.262	69.00	82.50	603540001	3468	
			72.762	86.262	82.00	95.50	603540002		
			85.762	99.262	95.00	108.50	603540003		
			98.762	112.262	108.00	121.50	603540004		
		20mm (.787")	59.762	73.262	69.00	82.50	603542001		3467
			72.762	86.262	82.00	95.50	603542002		
			85.762	99.262	95.00	108.50	603542003		
			98.762	112.262	108.00	121.50	603542004		
45mm (1.772")	25.4mm (1.000")	16mm (.630")	59.762	73.262	69.00	82.50	604530001	3468	
			72.762	86.262	82.00	95.50	604530002		
			85.762	99.262	95.00	108.50	604530003		
			98.762	112.262	108.00	121.50	604530004		
		20mm (.787")	59.762	73.262	69.00	82.50	604532001		3467
			72.762	86.262	82.00	95.50	604532002		
			85.762	99.262	95.00	108.50	604532003		
			98.762	112.262	108.00	121.50	604532004		
60mm (2.362")	25.4mm (1.000")	16mm (.630")	59.762	73.262	69.00	82.50	606030001	3468	
			72.762	86.262	82.00	95.50	606030002		
			85.762	99.262	95.00	108.50	606030003		
			98.762	112.262	108.00	121.50	606030004		
		20mm (.787")	59.762	73.262	69.00	82.50	606032001		3467
			72.762	86.262	82.00	95.50	606032002		
			85.762	99.262	95.00	108.50	606032003		
			98.762	112.262	108.00	121.50	606032004		

AmesburyTruth™
Engineered Solutions. Trusted Results.

THE INFORMATION CONTAINED IN THIS DRAWING IS CONFIDENTIAL AND PROPRIETARY. THIS DRAWING IS NOT TO BE COPIED OR REPRODUCED IN WHOLE OR IN PART WITHOUT EXPRESS WRITTEN PERMISSION.

INTERPRET PER:
ASME Y14.5M-2009
UNITS: INCH

THIRD ANGLE
PROJECTION

CUSTOMER PAGE

DRAWING TITLE:
P3000 ACTIVE 3 POINT 2 SHOOTS

SCALE: .4
PART #:
P3000 ACTIVE 3 POINT 2 SHOOTS

SHEET 1 OF 1