



NOTES:

1. NOT FOR USE ON AWNING WINDOWS.
2. SEE OPERATOR/HINGE COMPATABILITY INFORMATION GIVEN FOR EACH OPERATOR. SEE RESPECTIVE CATALOG PAGE FOR OPERATOR OF YOUR CHOICE.
3. RECOMMENDED SCREWS PER PAIR OF HINGE:  
 SASH ARM- (QTY 8) #7 X .750 PHILLIPS FLAT HEAD, STEEL, SHEET METAL SCREWS.  
 TRACK- (QTY 6) #7 X .750 PHILLIPS FLAT HEAD, UNDERCUT,SST, SHEET METAL SCREWS,

CUSTOMER PAGE

<p><b>Amesbury Truth</b> Engineered Solutions. Trusted Results.</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS CONFIDENTIAL AND PROPRIETARY. THIS DRAWING IS NOT TO BE COPIED OR REPRODUCED IN WHOLE OR IN PART WITHOUT EXPRESS WRITTEN PERMISSION.</p>	<p>INTERPRET PER: ASME Y14.5M-2009</p> <p>UNITS: INCH</p>	<p>DRAWING TITLE: 14.05.00.261 CUSTOMER PAGE</p>
	<p>THIRD ANGLE PROJECTION</p>	<p>SCALE: 1:1</p> <p>DRAWING #: 14.05.00.261 CUSTOMER PAGE</p>
		<p>SHEET 1 OF 1</p>