



| TE BAR ASSEMBLY | QTY | 13000.92 | 13003.92 | 81.44 | 24.403 | 24.403 | 24.403 |
|-----------------|-----|----------|----------|-------|--------|--------|--------|
| 87.87~93.86" | 4 | 13000.92 | 13001.92 | 74.44 | 22.403 | 22.403 | 22.403 |
| 81.87~87.86" | 4 | 12897.92 | 12898.92 | 68.44 | 20.403 | 20.403 | 20.403 |
| 75.87~81.86" | 3 | 12998.92 | 12999.92 | 63.44 | 27.905 | 27.905 | |
| 69.87~75.86" | 3 | 12891.92 | 12892.92 | 57.44 | 24.905 | 24.905 | |
| 63.87~69.86" | 3 | 12891.92 | 12892.92 | 51.44 | 21.905 | 21.905 | |
| 57.87~63.86" | 2 | 12887.92 | 12888.92 | 45.44 | 18.905 | 18.905 | |
| 51.87~57.86" | 3 | 12893.92 | 12894.92 | 39.44 | 15.905 | 15.905 | |
| 45.87~51.86" | 2 | 12885.92 | 12886.92 | 33.44 | 13.910 | 13.910 | |
| 39.87~45.86" | 2 | 12883.92 | 12884.92 | 27.44 | 11.910 | 11.910 | |
| 33.87~39.86" | 2 | 12879.92 | 12880.92 | 21.44 | 13.810 | 13.810 | |
| 27.87~33.86" | 1 | 12877.92 | 12878.92 | 15.44 | 13.888 | 13.888 | |
| 21.87~27.86" | 1 | 12875.92 | 12876.92 | 9.44 | 17.403 | 17.403 | |

| PART NO. | QUANTITY | DESCRIPTION | | |
|---------------|----------|-------------|----|---|
| 19178 | 2 | 4 | 4 | SCREW 8X1 PH PH SMS 16-6 SS (SECURE KEEPERS) |
| 19077.92 | 7 | 9 | 11 | SCREW 6X1 T17 PH PH SMS 10-7 (TE BAR GLIDES AND LOCK DRIVE) |
| 19178 | 2 | 2 | 2 | SCREW 8X1 PH PH SMS 16-6 SS (ROUND TOP KEEPERS) |
| 19005 | 2 | 2 | 2 | SCREW 6-32X3/8 T22 PH PH SMS 10-7 (CONNECTING LINK) |
| 33593.00.0500 | 1 | 1 | 1 | KEEPER LH FLANGE SS (33593.00.0500 RH) |
| 12667.92 | 1 | 1 | 1 | ROUND TOP TE BAR ASSY |
| 41392 | 3 | 3 | 3 | GUIDE TE BAR SINGLE |
| 45459.9P | 1 | 1 | 1 | CONNECTING LINK |
| 12662 | 1 | 1 | 1 | ENCORE TANGLO HANDLE AND ESCUTCHEON |
| SEE CHART | 1 | 1 | 1 | ENCORE TE BAR ASSEMBLY |
| 33593.00.0500 | 1 | 2 | 3 | KEEPER LH FLANGE SS (33593.00.0500 RH) |
| 12642 | 1 | 1 | 1 | ENCORE LOCK DRIVE ASSEMBLY |

- NOTES:
- ACCURACY OF INDICATED DIMENSIONS IS CRITICAL TO THE FUNCTION OF THE MULTIPART LOCK.
 - "A", "B" AND "C" DIMENSIONS ARE CONSIDERED TO GIVE SEQUENTIAL LOCKING, STARTING WITH THE BOTTOM LOCKING POINT.
 - TE BAR MOVES APPROX. 1.50"
 - CONTACT TECHNICAL SERVICES FOR TE BAR INFORMATION.
 - ROUND TOP TE BAR HAS APPROX. A 1/2 INCH RADIUS. IT MUST BE FORMED TO MATCH THE RADIUS OF THE WINDOW FRAME BEING INSTALLED ON.